



EMMYWATCH
VINTAGE RESTORATIONS

Favre Leuba 253 Movement Parts (1)

Compiled by EmmyWatch - <https://www.emmywatch.com>

Calibre de base

Remontage manuel

Seconde au centre directe
 Ø d'encageage: 25,60 mm
 Hauteur maximum: 3,00 mm
 17 rubis
 Système antichoc au balancier
 18 000 alternances par heure

Hand winding


Sweep second
 Ø of movement: 25,60 mm
 Maximum height: 3,00 mm
 17 jewels
 Shock-protecting device at the balance
 18 000 vibrations per hour

Para dar cuerda a mano

Segundero central
 Extensión: 25,60 mm
 Altura máxima: 3,00 mm
 17 rubies
 Dispositivo amortiguador al volante
 18 000 alternancias por hora

Hand-Aufzug

Zentrumsekunde
 Werkdurchmesser: 25,60 mm
 Höhe max.: 3,00 mm
 17 Steine
 Stoss-Sicherung an der Unruh
 18 000 Halbschwingungen stündlich



EMMYWATCH

100	105	110	121/1	125	126			
*172/1	*172/2	181	197/1	206	210	227	228	
245	255	260	307/1	*324	*325	364	374	401
407	410	420	422	425	430	435	440	443
445	*450	*452	705	710	721	*728	*730/1	770

Echelle/Scale 1:1 *Echelle/Scale 3:1

5101	5102	5105 5110 5121/1	5125 5126	5374	5420	5425	5445	5452	5750

Echelle/Scale 3:1