




## Jaegar Lecoultre 819 Movement Parts (1)

*Compiled by EmmyWatch - <https://www.emmywatch.com>*



Calibre avec seconde au centre  
 17 pierres — Parechoc  
 18 000 alternances heure  
 Balancier sans vis: Ø 8,54 mm.  
 Diamètre encageage: 20,80 mm.  
 Hauteur totale: 3,44 mm.  
 Ø filetage tige de remontoir 0,90 mm.  
 Dimensions ressort de braillet:  
 L. 2.70 mm. H. 0,90 mm. E: 0,09 mm.

**CAL. 819**  
**BASE: CAL. 818**

**LE COULTRE**



205



214



220



275



283



471



5471

Ech.-Scale 3 : 1.

- 205 Roue de centre percée, avec  
 chaussée (Indiquer hauteur de  
 chaussée)  
 214 Roue moyenne, long pivot  
 220 Roue de seconde  
 275 Pignon de seconde au centre  
 283 Roue entraîneuse sur roue  
 moyenne  
 471 Ressort friction du pignon de  
 seconde au centre  
 5471 Vis ressort friction du pignon de  
 seconde au centre  
 605 Pierre de roue moyenne dessus

#### Fournitures non illustrées

- 245 Chaussée pour seconde au  
 centre (indiquer hauteur)  
 255 Roue des heures pour seconde  
 au centre

- 205 Center wheel and pinion, drilled,  
 with cannon pinion (Indicate  
 height of cannon pinion)  
 214 Third wheel and pinion, long pivot  
 220 Fourth wheel and pinion  
 275 Sweep second pinion  
 283 Driving wheel over third wheel  
 471 Friction spring of the sweep second  
 pinion  
 5471 Friction spring screw  
 605 Jewel for third wheel, upper

#### Materials not illustrated

- 245 Cannon pinion for sweep second  
 (Indicate height)  
 255 Hour wheel for sweep second

Toutes les autres fournitures du Cal. 819 sont identiques  
 à celles du Cal. 818

All other materials for Cal. 819 are identical  
 to those of Cal. 818.