





Seiko 6119C Movement Parts (1)

Compiled by EmmyWatch - <https://www.emmywatch.com>



Cal. 6119C

Characteristics

Casing diameter: 27.00 ϕ mm

Maximum height: 5.15 mm

Vibrations per hour: 21,600

Automatic winding with sweep second

Calendar (day & date)

Instant setting device for day & date calendar

Bilingual change-over system for day of week

"Diashock" Shock Resistant Device

"Diafix" Oil Lubrication Device



112521 171612 251613 341612 345612 387613 015411 011206 015113



☆357612 ☆998613 ☆999611 193527 500620 823619 556611 802611



808611 810611 868611 ☆801611 ☆870558 880611 572610



022269 022458 022493 022761 2/1

☆ ⇨ Please see remarks on the next page.
As for all other parts not shown here, please refer to the basic calibre
(Cal. No. 6106A 25J Catalog No. 61-06-1 Green page).

Calibre No.		Jewels	Style Name	
6119C		21j		
⇨ Basic Calibre 6106A 25J Catalog No. 61-06-1				
PART NO.	LIST OF MATERIALS		PART NO.	LIST OF MATERIALS
112521	Barrel & train-wheel bridge		883610	Date corrector spring
122612	Center wheel bridge		☆884611	Holding ring for dial
161805	Pallet cock		963610	Snap for day star with dial disk
171612	Balance cock		972610	Day-date corrector finger
193527	Framework for automatic device with ball-bearing		022150	Stud screw
205613	Complete barrel with arbor		022252	Holder screw for transmission wheel & pawl lever
213612	Barrel arbor		022257	Date corrector spring screw
224611	Center wheel & pinion with cannon pinion		022269	Minute wheel bridge screw (Cheese-head screw)
225611	Cannon pinion		022351	Center wheel bridge screw
231610	Third wheel & pinion		022458	Screw for oscillating weight
241611	Sweep second wheel & pinion		022467	Ratchet wheel screw
251613	Escape wheel & pinion		022468	Pallet cock screw
261611	Minute wheel		022470	Framework screw for automatic device with ball-bearing
271611	Hour wheel		022471	Click screw
281611	Setting wheel		022493	Bridge screw
282611	Clutch wheel		022662	Setting lever spring screw
285611	Ratchet wheel		022677	Screw for day & date driving wheel
301611	Jewelled pallet fork & staff		022760	Minute wheel bridge screw (Chamfer-head screw)
310611	Balance complete with stud		022760	Date dial guard screw
315611	Balance staff		022761	Dial screw
331610	Roller with jewel		011145	Upper hole jewel for center wheel
341612	Regulator		011146	Lower hole jewel for center wheel
345612	Stud holder		011306	Upper hole jewel for 3rd wheel
354615	Winding stem		011306	Lower hole jewel for 3rd wheel
☆357612	Click		011306	Upper hole jewel for sweep second wheel
381611	Setting lever with axle		011503	Upper hole jewel for pallet
383611	Yoke (Clutch lever)		011503	Lower hole jewel for pallet
384611	Minute wheel bridge		011147	Upper hole jewel for transmission wheel
388611	Setting lever spring		011147	Lower hole jewel for transmission wheel
☆397610	Lever for unlocking stem		023150	Tube for pallet cock screw (Cylinder type)
401615	Mainspring with slipping attachment		023151	Tube for bridge screw
☆998613	Indicator wheel		023170	Tube for pallet cock screw (Recessed type)
☆999611	Indicator wheel spring		023171	Tube for framework screw of automatic device
014363	Diashock upper frame		023417	Date corrector pin
014364	Diashock lower frame			
014365	Diashock hole jewel with frame			
011210	Diashock cap jewel			
014317	Diashock spring			
015411	Diafix upper hole jewel with frame for escape wheel			
015411	Diafix lower hole jewel with frame for escape wheel			
011206	Diafix cap jewel			
015113	Diafix spring			
500620	Oscillating weight			
505611	Transmission wheel			
823619	Eccentric post			
831611	Pawl lever with jewel			
839610	Holder for transmission wheel & pawl lever			
556611	Date finger			
☆801611	Date dial			
802611	Date driving wheel			
808611	Date dial guard			
810611	Date jumper			
817610	Intermediate date wheel			
868611	Day finger			
☆870558	Day star with dial disk (English ↔ Spanish)			
880611	Date corrector			

☆ ⇨ Please see remarks on the next page.
Items in light letters are not shown in photos; those parts are interchangeable with the basic calibre
(Cal. No. 6106A 25J Catalog No. 61-06-1 Green page).

Calibre No.	6119C	Jewels	21j	Style Name
↔ Basic Calibre 6106A 25J Catalog No. 61-06-1				
Remarks:				
Winding stem (☆ 357612) Indicator wheel (☆ 998613) Indicator wheel spring (☆ 999611) These parts are available only for watches with rotating dial ring.				
Lever for unlocking stem ☆ 397610 Used only for the one-piece waterproof case. If the lever for unlocking stem is required in any other type, specify the dial No. or the case No.				
Date dial ☆ 801611 (White figures on black background) Used when the crown is located at 4 o'clock and the date frame at 3 o'clock. If the date dial is required in any other type, specify ① Cal. No. ② the crown position ③ the date frame position and ④ the dial No.				
Day star with dial disk ☆ 870558 (English ↔ Spanish) Used when the crown is located at 4 o'clock and the day frame at 3 o'clock. When ordering any other type of the day star with dial disks, clearly mention the number printed on the disk. If the number is unknown, specify ① Cal. No. ② the crown position ③ the day frame position ④ the dial No. and ⑤ the national language.				
Holding ring for dial ----- Measure the total thickness and the outside diameter ----- ☆ 884611 1.8mm total thickness and 29.1 φmm outside diameter If the holding ring for dial is required in any other type, specify ① Cal. No. and ② the dial No.				

EMMYWATCH
VINTAGE RESTORATIONS