



Seiko 6308A Movement Parts (1)

Compiled by EmmyWatch - <https://www.emmywatch.com>

Calibre No.


6308A

Jewels


17j

Style Name

⇒ Basic Calibre 6309A 17J Catalog No. 63-09-1



Cal. 6308A



Characteristics

Casing diameter : 27.0 ϕ mm
 Maximum height : 5.2 mm
 Vibrations per hour : 21,600
 Automatic winding with sweep second
 Calendar (date)
 Instant date setting
 "Diashock" Shock Resistant Device



112 601




122 602




161 805



171 611



193 603



205 613



213 612



221 611



225 611



231 601



241 611



251 611



261 611



271 611



282 601



285 611



301 611




311 601



341 601



345 601



354 601



381 601



383 601



384 601



387 602



388 601



390 601



☆397 601




☆397 602



401 615



☆500 601



505 601



802 601



803 601



808 601



808 602



810 601



817 611




831 611



839 601



868 601



☆884 931



011 145



011 146



011 147



011 210



011 406



011 503



011 532



011 723



011 724



014 317



014 363



014 364



014 365



023 039



023 040



023 150



023 151



022 257



022 458



022 467



022 468



022 491



022 493



022 760



022 761



022 160

Calibre No. 6308A		Jewels 17j	Style Name
⇨ Basic Calibre 6309A 17J Catalog No. 63-09-1			
PART NO.	PART NAME	PART NO.	PART NAME
112 601	Barrel & train-wheel bridge	022 257	Setting lever spring screw
122 602	Center wheel bridge	022 458	Screw for oscillating weight
161 805	Pallet cock	022 467	Ratchet wheel screw
171 611	Balance cock	022 468	Pallet cock screw
193 603	Framework for automatic device with ball-bearing	022 468	Framework screw for automatic device with ball-bearing
205 613	Complete barrel with arbor	022 468	Date driving wheel screw
213 612	Barrel arbor	022 491	Minute wheel bridge screw
221 611	Center wheel & pinion	022 493	Barrel & train wheel bridge screw
225 611	Cannon pinion	022 493	Balance cock screw
231 601	Third wheel & pinion	022 760	Date dial guard screw
241 611	Fourth wheel & pinion	022 761	Dial screw
251 611	Escape wheel & pinion	022 160	Stud screw
261 611	Minute wheel	023 039	Tube for framework screw of automatic device
271 611	Hour wheel	023 040	Tube for pallet cock screw (recessed type)
282 601	Clutch wheel	023 150	Tube for pallet cock screw (cylinder type)
285 611	Ratchet wheel	023 151	Tube for barrel & train wheel bridge screw
301 611	Jewelled pallet fork & staff		
311 601	Balance complete		
341 601	Regulator		
345 601	Stud holder		
354 601	Winding stem		
381 601	Click		
383 601	Setting lever		
384 601	Yoke (Clutch lever)		
387 602	Minute wheel bridge		
388 601	Setting lever spring		
390 601	Setting lever axle		
☆397 601	Lever for unlocking stem A		
☆397 602	Lever for unlocking stem B		
401 615	Mainspring with slipping attachment		
☆500 601	Oscillating weight		
505 601	Transmission wheel		
☆801 601	Date dial		
802 601	Date driving wheel		
803 601	Setting wheel lever complete		
808 601	Date dial guard A		
808 602	Date dial guard B		
810 601	Date jumper		
817 611	Intermediate date wheel		
831 611	Pawl lever with jewel		
839 601	Holder for transmission wheel & pawl lever		
868 601	Date driving wheel holder		
☆884 931	Holding ring for dial		
011 145	Upper hole jewel for center wheel		
011 146	Lower hole jewel for center wheel		
011 147	Upper hole jewel for transmission wheel		
011 210	Diashock cap jewel		
011 406	Upper hole jewel for escape wheel		
011 406	Lower hole jewel for escape wheel		
011 503	Upper hole jewel for pallet		
011 532	Lower hole jewel for third wheel		
011 723	Lower hole jewel for pallet		
011 724	Lower hole jewel for transmission wheel		
014 317	Diashock spring		
014 363	Diashock upper frame		
014 364	Diashock lower frame		
014 365	Diashock hole jewel with frame		
022 257	Center wheel bridge screw		

☆⇨ Please see remarks on the next page.

Calibre No.

6308A

Jewels

17j

Style Name

⇒ Basic Calibre **6309A** 17J Catalog No. 63-09-1**Remarks :****Lever for unlocking stem**

- ☆397 601.....Used for the one-piece type case with the dial whose external diameter is **27mm** or longer.
(When the dial is shaped other than round, the radius is to be measured in the direction of the lever for unlocking stem.)
- ☆397 602.....Used for the one-piece type case with the dial whose external diameter is less than **27mm**.
(When the dial is shaped other than round, the radius is to be measured in the direction of the lever for unlocking stem.)

Date dial

- ☆801 601 (Black figures on white background).....Used when both the crown and the calendar frame are located at **3 o'clock** position.

If in any other type of date dial is required, specify ① Cal. No. ② the crown position ③ the calendar frame position and ④ the dial No.

Holding ring for dial


- ☆884 931.....The type of a holding ring for dial is determined based on the design of cases and dials. Check the case number and refer to **"SEIKO Casing Parts List"** to choose a corresponding holding ring for dial.

Oscillating weight

- ☆500 601.....This oscillating weight is interchangeable with the one for movements of calibre 61 series listed below, and the interchangeability is limited within the listed calibres.

Oscillating weight Cal. No.	500 620	500 622	500 601
6105 A & B			
6106 B & C			
6117 A & B	V	V	V
6118A			
6119 B & C			
6109A	V	V	V
63 Series	—	—	V


V : Interchangeable
— : Not interchangeable

Form of oscillating weight

500 620



500 622



500 601